Claims

[c1]	
	1. A system for encrypting packets on a network comprising:
	A. a plurality of network nodes;
	B. a communication channel between said plurality of network nodes;
	C. one or more packets sent between said plurality of network nodes over said communication channel;
	D. wherein said one or more packets contain an encryption key identifier and a payload
	E. one or more encryption keys stored on one or more of said plurality of network nodes; and
	F. a system for encrypting said payload based on said encryption key identifier and said
	one or more encryption keys.

[c2]	
	2. A system for encrypting packets on a network as recited in claim 1, wherein said
	payload is only partially encrypted.
[c3]	·
	3. A system for encrypting packets on a network as recited in claim 1, wherein said one
	or more packets contains a destination address.
[c4]	
	4. A system for encrypting packets on a network as recited in claim 1, wherein said
	encryption key identifier contains a value indicating "no encryption".
[c5]	
	5. A system for encrypting packets on a network as recited in claim 4, wherein
	information external to the said payload is used to select said encryption key identifier.

6. A system for encrypting packets on a network as recited in claim 1, wherein said

[c6]

[c7]

7. A system for encrypting packets on a network as recited in claim 6, wherein said one or more fields are selected from the group consisting of a socket, a protocol identifier, a node address, a network address, a sub-network address, a service type, and a packet identifier.

[c8]

8. A system for encrypting packets on a network as recited in claim 6, wherein said one or more fields are selected from the group consisting of the application layer, the presentation layer, the session layer, the transport layer, the network layer, the data link layer, and the physical layer.

[c9]

9. A system for encrypting packets on a network as recited in claim 1, wherein said communication channel is a network selected from the group consisting of a wireless network, a light frequency network, a power line network, an acoustic network and a wired network.

[c10]

10. A system for decrypting packets on a network comprising:

	B. a communication channel between said plurality of network nodes;
	C. one or more packets sent between said plurality of network nodes over said
	communication channel;
	D. wherein said one or more packets further comprises an encryption key identifier and
	a payload;
	E. one or more encryption keys stored on one or more of said plurality of network
	nodes; and '
	F. a system for decrypting said payload based on said encryption key identifier and said
	one or more encryption keys.
[c11]	
	11. A system for decrypting packets on a network as recited in claim 10, wherein said
	payload is only partially decrypted.
[c12]	

A. a plurality of network nodes;

	12. A system for decrypting packets on a network as recited in claim 10, wherein said
	one or more packets further comprises a destination address.
[c13]	
	13. A system for decrypting packets on a network as recited in claim 10, wherein said
	communication channel is a network selected from the group consisting of, a wireless
	network, a light frequency network, a power line network, an acoustic network and a
	wired network.
[c14]	
	14. A system for encrypting packets on a network comprising:
	A. a plurality of network nodes;
	B. a communication channel between said plurality of network nodes;
	C. one or more packets forming a packet group which are sent on said communication
	channel between said plurality of network nodes;
	D. said packet group further comprising an encryption key identifier and a payload;

	E. one or more encryption keys for occurrences of said encryption key identifier; and
	F. a system for encrypting said payload based on said encryption key identifier and said
	one or more encryption keys.
[c15]	
	15. A system for encrypting packets on a network as recited in claim 14, wherein said
	payload is only partially encrypted.
[c16]	
	16. A system for encrypting packets on a network as recited in claim 14, wherein said
	one or more packets further comprises a destination address.
[c17]	
	17. A system for encrypting packets on a network as recited in claim 14, wherein said
	encryption key identifier further comprises a value indicating "no encryption".
[c18]	

18. A system for encrypting packets on a network as recited in claim 17, wherein information external to the packet payload is used to select said encryption key identifier.

[c19]

19. A system for encrypting packets on a network as recited in claim 14, wherein said payload further comprises one or more fields that are used to select said encryption key identifier.

[c20]

20. A system for encrypting packets on a network as recited in claim 19, wherein said field is selected from the group consisting of a socket, a protocol identifier, a node address, a network address, a sub-network address, a service type, and a packet identifier.

[c21]

21. A system for encrypting packets on a network as recited in claim 19, wherein said field is selected from the group consisting of the application layer, the presentation layer, the session layer, the transport layer, the network layer, the data link layer, and the physical layer.

[c22]

	22. A system for encrypting packets on a network as recited in claim 14, wherein said
	communication channel is a network selected from the group consisting of, a wireless
	network, a light frequency network, a power line network, an acoustic network and a
	wired network.
[c23]	
	23. A system for decrypting packets on a network comprising:
	A. a plurality of network nodes;
	B. a communication channel between said plurality of network nodes;
	C. one or more packets forming a packet group which are sent on said communication
	channel between said plurality of network nodes;
	D. said packet group further comprising an encryption key identifier and a payload;
	E. one or more encryption keys; and

	F. a system for decrypting said payload based on said encryption key identifier and said
	one or more encryption keys.
[c24]	·
	24. A system for decrypting packets on a network as recited in claim 23, wherein said
	payload is only partially decrypted.
[c25]	
	25. A system for decrypting packets on a network as recited in claim 23, wherein said
	one or more packets further comprising a destination address.
[c26]	
	26. A system for encrypting packets on a network as recited in claim 23, wherein
	communication channel is a network selected from the group consisting of, a wireless
	network, a light frequency network, a power line network, an acoustic network and a
	wired network.
[c27]	
	27. A method for encrypting packets on a network comprising:
	A. selecting an encryption key and an associated encryption key identifier;

	B. encrypting data to form a payload using said encryption key;
	C. building a packet comprising said payload and said encryption key identifier; and
	D. sending said packet from a sending network node across a communication channel.
[c28]	
	28. A method for encrypting packets on a network as recited in claim 27, wherein said
	packet is build with a payload that is partially encrypted.
[c29]	
	29. A method for encrypting packets on a network as recited in claim 27, wherein said packet is built further comprising a destination address.
[c30]	packet is built further comprising a destination address.
	30. A method for encrypting packets on a network as recited in claim 27, wherein said
	packet is built with an encryption key identifier which indicates no encryption.
[c31]	

31. A method for encrypting packets on a network as recited in claim 30, wherein selection of said encryption key identifier is based on information external to said payload.

[c32]

[c33]

- 32. A method for encrypting packets on a network as recited in claim 27, wherein selection of said encryption key identifier is based on information within said payload.
 - 33. A method for encrypting packets on a network as recited in claim 32, wherein selection of said encryption key identifier is based on fields within said payload selected from the group consisting of a socket, a protocol identifier, a node address, a network address, a sub-network address, a service type, and a packet identifier.

[c34]

34. A method for encrypting packets on a network as recited in claim 27, wherein selection of said encryption key identifier is based on protocol layers within said payload selected from the group consisting of the application layer, the presentation layer, the session layer, the transport layer, the network layer, the data link layer, and the physical layer.

[c35]

35. A method for encrypting packets on a network as recited in claim 27, wherein said packet is sent on communication channel selected from the group consisting of a wireless network, a light frequency network, a power line network, an acoustic network and a wired network.

[c36]

- 36. A method for decrypting packets on a network comprising:
- A. receiving a packet on a communication channel wherein said packet further comprises an encryption key identifier and a payload; and
- B. decrypting said payload by using an encryption key which is indicated by said encryption key identifier.

[c37]

37. A method for decrypting packets on a network as recited in claim 36, wherein only part of said payload is decrypted.

[c38]

38. A method for decrypting packets on a network as recited in claim 36, wherein said packet further comprises a destination address.

[c39]

39. A method for decrypting packets on a network as recited in claim 36, wherein said packet is received on a communication channel selected from the group consisting of a wireless network, a light frequency network, a power line network, an acoustic network and a wired network.

[c40]

- 40. A method for encrypting packets on a network comprising:
- A. selecting an encryption key and an associated encryption key identifier;
- B. encrypting data with said encryption key which forms one or more payloads;
- C. building one or more packets which form a packet group from said one or more payloads wherein a packet from said packet group further comprises an encryption key identifier which identifies said encryption key; and

	D. sending said packet group from a sending network node across a communication
	channel.
[c41]	
[0.11]	
	41. A method for encrypting packets on a network as recited in claim 40, wherein said
	one or more payloads are partially encrypted.
[c42]	
	42. A method for encrypting packets on a network as recited in claim 40, wherein said
	one or more packets are built with a destination address.
[c43]	
	43. A method for encrypting packets on a network as recited in claim 40, wherein said
	encryption key identifier indicates no encryption.
[c44]	
	44. A method for encrypting packets on a network as recited in claim 43, wherein
	selection of said encryption key identifier is based on information external to said
	payload.
	E-1

[c45]

45. A method for encrypting packets on a network as recited in claim 40, wherein selection of said encryption key identifier is based on information within said payload.

[c46]

46. A method for encrypting packets on a network as recited in claim 45, wherein selection of said encryption key identifier is based on fields within said payload selected from the group consisting of a socket, a protocol identifier, a node address, a network address, a sub-network address, a service type, and a packet identifier.

[c47]

47. A method for encrypting packets on a network as recited in claim 40, wherein selection of said encryption key identifier is based on protocol layers within said payload selected from the group consisting of the application layer, the presentation layer, the session layer, the transport layer, the network layer, the data link layer, and the physical layer.

[c48]

48. A method for encrypting packets on a network as recited in claim 40, wherein said packet group is sent on a communication channel selected from the group consisting of a wireless network, a light frequency network, an acoustic network, a power line network, and a wired network.

[c49]

49. A method for decrypting packets on a network comprising:

A. receiving one or more packets which form a packet group on a communication channel wherein said packet group further comprises an encryption key identifier and one or more payloads; and

B. decrypting said one or more payloads using an encryption key which is indicated by said encryption key identifier.

[c50]

50. A method for decrypting packets on a network as recited in claim 49, wherein only part of said one or more payloads is decrypted.

[c51]

51. A method for decrypting packets on a network as recited in claim 49, wherein said one or more packets further comprises a destination address.

[c52]

52. A method for decrypting packets on a network as recited in claim 49, wherein said packet is received on communication channel selected from the group consisting of a wireless network, a light frequency network, a power line network, an acoustic network and a wired network.